



## Īpašības

- Vacuum generator with integrated control valves and system monitoring functions
- Gripping and blowing off can be controlled without the need for external valves
- Optimised air consumption thanks to many models with differing suction capacities
- Minimum energy costs in continuous operation
- Easy adjustment with foil keypad and LED display of the settings
- Minimum size, low weight
- Optimum vacuum generation directly on the suction pad
- Complete solution for very simple installation
- Short learning curve thanks to "teach" function
- No need for additional sensors
- Easily visible status indication
- Izmantošana
- Ideal where space is restricted and for highly dynamic movements, handling with industrial robots, linear axes
- pick-and-place systems
- Iztukšošanas pakāpe
- 85 %
- Pamatkorpuss
- Anodised aluminium
- Iebūvēts
- NC blow-off valve, filter, silencer, non-return valve

## Apraksts

Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Iztukšošanas pakāpe %	Sprauslu izmērs	Iesūkšanas vārsts miera stāvoklī	Saspīestā gaisa pieslēgums	Vakuuma pieslēgums	Sūkšanas gaisa patēriņš l/min	maks. sūkšanas apmērs l/min	Ekspluatācijas spiediens bar	
K- 07 45 01 46	85	01	NC	M 5 IG	M5 female	46.0	23.0	4.5	65 10 10
K- 07 45 01 45	85	01	NO	M 5 IG	M5 female	46.0	23.0	4.5	65 10 10