

Spring plungers



Izmantošana

Handling of workpieces with differing heights (eg. Curved metal sheets)

Handling of very sensitive workpieces, very soft landing is assured

Temperatūra maks.

80 °C

Temperatūra min.

0 °C

Sūcēja pieslēgums

M 3 female

Amortizācijas gājiens

5.0 mm

Modelis

Spring plunger with high-strength steel rod, guide sleeve and lower damping spring

Plunger rod with integrated vacuum guide

## Apraksts

Suitable for all round or oval suction pads in our standard range.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vakuuma pieslēgums	Amortizācijas gājiens mm	Garums mm	Vertikālā noslodze N/m <sup>2</sup>
K- 07 45 00 73	M 3 female	5.0	33.5	550
K- 07 45 00 76	M 5 female	5.0	41.2	1.500
K- 07 45 00 74	M 5 female	10.0	47.2	1.500
K- 07 45 00 75	M 5 female	20.0	59.2	1.500
K- 07 45 00 70	G 1/8 female	15.0	80.0	3.700
K- 07 45 00 67	G 1/8 female	25.0	95.0	3.700
K- 07 45 00 71	G 1/8 female	25.0	93.0	3.700
K- 07 45 00 68	G 1/8 female	50.0	124.5	2.400
K- 07 45 00 72	G 1/8 female	50.0	124.0	2.400
K- 07 45 00 69	G 1/8 female	75.0	154.0	2.400