



Izmantošana

Handling of workpieces with differing heights (eg. Curved metal sheets)

Handling of very sensitive workpieces, very soft landing is assured

Temperatūra maks.

80 °C

Temperatūra min.

0 °C

Sūcēja pieslēgums

M 3 female

Amortizācijas gājiens

5.0 mm

Modelis

Spring plunger with high-strength steel rod, guide sleeve and lower damping spring

Plunger rod with integrated vacuum guide

Apraksts

Suitable for all round or oval suction pads in our standard range.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vakuuma pieslēgums	Amortizācijas gājiens mm	Garums mm	Vertikālā noslodze N/m ²
K- 07 45 00 73	M 3 female	5.0	33.5	550
K- 07 45 00 76	M 5 female	5.0	41.2	1.500
K- 07 45 00 74	M 5 female	10.0	47.2	1.500
K- 07 45 00 75	M 5 female	20.0	59.2	1.500
K- 07 45 00 70	G 1/8 female	15.0	80.0	3.700
K- 07 45 00 67	G 1/8 female	25.0	95.0	3.700
K- 07 45 00 71	G 1/8 female	25.0	93.0	3.700
K- 07 45 00 68	G 1/8 female	50.0	124.5	2.400
K- 07 45 00 72	G 1/8 female	50.0	124.0	2.400
K- 07 45 00 69	G 1/8 female	75.0	154.0	2.400