


K-DRUCKVERST MANO H SCHALLD

VBA

Booster Regulator, pressure gauge, high-noise reduction silencer, VBA



Modelis
with pressure gauge and with high performance muffler
Darba vides
Saspiests gaiss
min. ekspluatācijas spiediens
0.20 MPa
maks. ieejas spiediens
0,1 to 1,0 MPa
Pneimatisko manometru pieslēgumu skaits
2
Pneimatiskā manometra pieslēgums
Rc 1/8
Vides temperatūra
+2 °C bis +50 °C
Vielas temperatūra
+2 °C to +50 °C

Apraksts

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

Produkts

Apzīmējums	Pneimatisko manometru pieslēgumu skaits	Pneimatiskais pieslēgums	Caurpl_de nom. l/min	maks. ekspluatācijas spiediens MPa	Spiediena iestatišanas mehānisms	Spiediena pastiprināšanas process	Ti
K- 07 60 00 11	2	G 3/8	1000	1.50	manually operated	1:2	3/8