



Modelis
with pressure gauge
Darba vides
Saspiests gaiss
min. ekspluatācijas spiediens
0.20 MPa
maks. ieejas spiediens
0,1 to 1,0 MPa
Pneimatisko manometru pieslēgumu skaits
2
Pneimatiskā manometra pieslēgums
Rc 1/8
Vides temperatūra
+2 °C bis +50 °C
Vielas temperatūra
+2 °C to +50 °C

Apraksts

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

Produkts

| Apzīmējums | Pneimatisko manometru pieslēgumu skaits | Pneimatiskais pieslēgums | Caurpl_de nom. l/min | Izmēģinājuma spiediens MPa | maks. ekspluatācijas spiediens MPa | Spiediena iestatišanas mehānisms | Spiediena pastiprināšanas process | Ti |
|----------------|---|--------------------------|----------------------|----------------------------|------------------------------------|----------------------------------|-----------------------------------|-----|
| K- 07 60 00 02 | 2 | G 1/4 | 230 | 3.00 | 2.00 | manually operated | 1:2 | 1/4 |
| K- 07 60 00 09 | 2 | G 3/8 | 1000 | 1.50 | 1.50 | manually operated | 1:2 | 3/8 |