


# K-DVST MIT REGLER

Pressure booster with regulator

**HANSA FLEX**  
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Ieejas spiediens  
2 - 10 bar  
Izejas spiediens  
Max. 20 bar (regulated: max. 16 bar)  
Temperatūras diapazons  
-10 °C to +50 °C (40 mm bore), -10 °C to +60 °C (63 mm bore)  
Darba vides  
Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.  
Blīvējums  
NBR  
Caurule  
Anodised aluminium jacket  
Korpuss  
Aluminium, anodised  
Spiediena regulators  
With plastic body  
Montāža  
Any position, with 4 mounting holes  
P2:P1  
1:1 to 1.6:1

## Apraksts

Pressure multipliers (boosters) allow a separate compressed air store with up to double pressure to be installed for selected devices in a compressed air system without an external energy source, i.e. it is possible to work with a maximum pressure of 20 bar in a standard 10 bar system (maximum ratio 2:1). This is achieved using a double piston, which is operated by a combination of integrated check valves in such a way that the booster works automatically until the target pressure is reached in a compressed air tank and is then automatically switched off. A tank is always required to build up the pressure and store the compressed air!

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Savienojums	Ø virzulim mm	H mm	L mm
K- 07 25 08 65	G 1/8"	40.0	139.0	194.0
K- 07 25 08 67	G 3/8"	63.0	183.0	290.0