

Filling valves (start-up valves)



Ieejas spiediens
2.5 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Korpuss
Material: Grivory® (PA 66)
Caurplūdes vērtības mērijums
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar
Pieslēguma vītne
Material: Die-cast zinc

Apraksts

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. These valves prevent a sudden build-up of pressure accompanied by dangerous, jerky cylinder movements. The full cross-section of the regulator is opened at 50% of the input pressure. The filling time can be altered by turning the adjusting screw.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm
K- 07 25 11 11	G 1/4	1300	52.0	78.0 mm	45.0	33.0
K- 07 25 11 12	G 3/8	1300	52.0	78.0 mm	45.0	33.0
K- 07 25 11 13	G 3/8	3400	63.0	111.5 mm	53.5	58.0
K- 07 25 11 14	G 1/2	3400	63.0	111.5 mm	53.5	58.0
K- 07 25 11 15	G 3/4	8750	85.0	112.0 mm	58.0	54.0
K- 07 25 11 16	G 1	8750	85.0	112.0 mm	58.0	54.0