

K-DRG DRV 200 STANDARD

DRV 200 pressure regulators, standard type



Ieejas spiediens
Max. 25 bar (Series 200 and 300 Series), Max. 40 bar (400 Series)
Temperatūras diapazons
Max. 75 °C
Samazināšanas process
Max. 10:1 (200 Series), Max. 20:1 (300 Series), Max. 6:1 (400 Series)
Blīvējums
NBR
Atsperes korpuss
Pressed brass up to DN 25, Grey cast iron from DN 32
Korpuss
Red brass 2.1096.01

Apraksts

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment. Good response characteristic because of only a few moving parts which hence minimal friction. Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m ³ /h	A mm	B	C mm	D mm
K- 07 25 04 86	G 1/4	1.5 - 8 bar	0.5	70.0	167.0 mm	120.0	47.0
K- 07 25 04 87	G 3/8	1.5 - 8 bar	0.6	70.0	168.0 mm	121.0	47.0
K- 07 25 04 88	G 1/2	1.5 - 8 bar	1.2	85.0	188.5 mm	142.0	46.5
K- 07 25 04 89	G 3/4	1.5 - 8 bar	1.3	85.0	189.5 mm	143.0	46.5
K- 07 25 04 90	G 1	1.5 - 8 bar	1.6	95.0	242.0 mm	186.0	56.0
K- 07 25 04 91	G 1 1/4	1.5 - 8 bar	4.2	104.0	323.0 mm	262.0	61.0
K- 07 25 04 92	G 1 1/2	1.5 - 8 bar	4.5	108.0	323.0 mm	262.0	61.0
K- 07 25 04 93	G 2	1.5 - 8 bar	7.2	146.5	376.0 mm	306.0	70.0