

# K-DRG DRVS MULTIFIX MINI

Pressure regulators with pressure supply at both ends



Ieejas spiediens  
Max. 16 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Atsperes korpuss  
POM-brass  
Korpuss  
Die-cast zinc  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the button down. &lt;br&gt;By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 28	G 1/4	0.1 - 3 bar	1200	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 29	G 1/4	0.2 - 6 bar	1200	40.0	85.0 mm	63.0	22.0	5	0
K- 07 25 00 27	G 1/4	0.5 - 10 bar	1200	40.0	85.0 mm	63.0	22.0	5	0