

Pressure regulators with pressure supply at both ends



Ieejas spiediens
Max. 25 bar
Vides temperatūra
Max. 50 °C
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc
Caurplūdes vērtības mērijums
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the knob down.
By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 04 33	G 1/4	0.5 - 6 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 34	G 1/4	0.5 - 10 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 35	G 1/4	0.5 - 16 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 36	G 3/8	0.5 - 6 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 37	G 3/8	0.5 - 10 bar	1800	48.0	98.0 mm	26.0
K- 07 25 04 38	G 3/8	0.5 - 16 bar	1800	48.0	98.0 mm	26.0