



Ieejas spiediens
Max. 28 bar
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR/TPU
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, painted silver
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators with self-relieving design in compact design. The pressure setting can be locked by pushing the knob down.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm	D mm	DN
K- 07 25 03 22	G 1/8	0.15 - 3.5 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 23	G 1/8	0.2 - 7.0 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 24	G 1/8	0.5 - 10.0 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 25	G 1/4	0.15 - 3.5 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 26	G 1/4	0.2 - 7.0 bar	340	43.0	72.5 mm	9.5	63.0	5
K- 07 25 03 27	G 1/4	0.5 - 10.0 bar	340	43.0	72.5 mm	9.5	63.0	5