

Pressure regulators for drinking water, DVGW approved



Ieejas spiediens
Max. 25 bar
Darba vietas
Drinking water, nitrogen, compressed air, non-aggressive liquids
Eksploatācijas temperatūra
Max. 40 °C (transparent strainer cup), Max. 70 °C (brass strainer cup)
Blīvējums
NBR
Atsperes korpuss
Plastic
Korpuss
Brass
Sietiņš
Plastic or brass

Apraksts

Diaphragm pressure regulators with pressure-reduced single-seated valve and built-in strainer. These pressure regulators, which are independent of inlet pressure, protect domestic water installations against excessive supply pressure. They can also be used for commercial or industrial purposes providing their specification is adequate.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m ³ /h	A mm	B	C mm	D mm
K- 07 25 04 57	R 1/2	1.5 - 6 bar	2.4	140.0	147.0 mm	89.0	58.0
K- 07 25 04 58	R 3/4	1.5 - 6 bar	3.1	160.0	147.0 mm	89.0	58.0
K- 07 25 04 59	R 1	1.5 - 6 bar	7.6	180.0	175.0 mm	111.0	64.0
K- 07 25 04 60	R 1 1/4	1.5 - 6 bar	9.1	200.0	175.0 mm	111.0	64.0
K- 07 25 04 61	R 1 1/2	1.5 - 6 bar	12.6	225.0	299.0 mm	173.0	126.0
K- 07 25 04 62	R 2	1.5 - 6 bar	12.0	255.0	299.0 mm	173.0	126.0
K- 07 25 04 63	R 1/2	1.5 - 12 bar	2.4	140.0	152.0 mm	96.0	56.0
K- 07 25 04 64	R 3/4	1.5 - 12 bar	3.1	160.0	152.0 mm	96.0	56.0
K- 07 25 04 65	R 1	1.5 - 12 bar	7.6	180.0	217.0 mm	140.0	77.0
K- 07 25 04 66	R 1 1/4	1.5 - 12 bar	9.1	200.0	217.0 mm	140.0	77.0
K- 07 25 04 67	R 1 1/2	1.5 - 12 bar	12.6	225.0	285.0 mm	172.0	113.0
K- 07 25 04 68	R 2	1.5 - 12 bar	12.0	255.0	285.0 mm	172.0	113.0
K- 07 25 04 69	R 1/2	0.5 - 2 bar	2.4	140.0	204.0 mm	148.0	56.0
K- 07 25 04 70	R 3/4	0.5 - 2 bar	3.1	160.0	204.0 mm	148.0	56.0
K- 07 25 04 71	R 1	0.5 - 2 bar	7.6	180.0	262.0 mm	185.0	77.0