

Pressure regulators for drinking water, DVGW approved



Ieejas spiediens  
Max. 25 bar  
Darba vietas  
Drinking water, nitrogen, compressed air, non-aggressive liquids  
Eksploatācijas temperatūra  
Max. 40 °C (transparent strainer cup), Max. 70 °C (brass strainer cup)  
Blīvējums  
NBR  
Atsperes korpuss  
Plastic  
Korpuss  
Brass  
Sietiņš  
Plastic or brass

## Apraksts

Diaphragm pressure regulators with pressure-reduced single-seated valve and built-in strainer. These pressure regulators, which are independent of inlet pressure, protect domestic water installations against excessive supply pressure. They can also be used for commercial or industrial purposes providing their specification is adequate.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m <sup>3</sup> /h	A mm	B	C mm	D mm
K- 07 25 04 57	R 1/2	1.5 - 6 bar	2.4	140.0	147.0 mm	89.0	58.0
K- 07 25 04 58	R 3/4	1.5 - 6 bar	3.1	160.0	147.0 mm	89.0	58.0
K- 07 25 04 59	R 1	1.5 - 6 bar	7.6	180.0	175.0 mm	111.0	64.0
K- 07 25 04 60	R 1 1/4	1.5 - 6 bar	9.1	200.0	175.0 mm	111.0	64.0
K- 07 25 04 61	R 1 1/2	1.5 - 6 bar	12.6	225.0	299.0 mm	173.0	126.0
K- 07 25 04 62	R 2	1.5 - 6 bar	12.0	255.0	299.0 mm	173.0	126.0
K- 07 25 04 63	R 1/2	1.5 - 12 bar	2.4	140.0	152.0 mm	96.0	56.0
K- 07 25 04 64	R 3/4	1.5 - 12 bar	3.1	160.0	152.0 mm	96.0	56.0
K- 07 25 04 65	R 1	1.5 - 12 bar	7.6	180.0	217.0 mm	140.0	77.0
K- 07 25 04 66	R 1 1/4	1.5 - 12 bar	9.1	200.0	217.0 mm	140.0	77.0
K- 07 25 04 67	R 1 1/2	1.5 - 12 bar	12.6	225.0	285.0 mm	172.0	113.0
K- 07 25 04 68	R 2	1.5 - 12 bar	12.0	255.0	285.0 mm	172.0	113.0
K- 07 25 04 69	R 1/2	0.5 - 2 bar	2.4	140.0	204.0 mm	148.0	56.0
K- 07 25 04 70	R 3/4	0.5 - 2 bar	3.1	160.0	204.0 mm	148.0	56.0
K- 07 25 04 71	R 1	0.5 - 2 bar	7.6	180.0	262.0 mm	185.0	77.0