


K-FLASCHENDRUCKR 200 N GASE

Pudeles spiediena regulators, pudeles spiediens 200 bar, nedegošām gāzēm



Satura manometrs

0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene

Materiāls

Presētais misiņš

Pudeles pieslēgums

Nut 3/4

Apraksts

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Gāzes veids	Ekspluatācijas spiediens bar
K- 07 25 07 11	Oxygen	0 - 10,0 bar
K- 07 25 07 12	Oxygen	0 - 20,0 bar
K- 07 25 07 14	Compressed air	0 - 10,0 bar
K- 07 25 07 15	Compressed air	0 - 20,0 bar
K- 07 25 07 16	Nitrogen	0 - 10,0 bar
K- 07 25 07 17	Nitrogen	0 - 20,0 bar
K- 07 25 07 18	Carbon dioxide	0 - 10,0 bar
K- 07 25 07 19	Carbon dioxide	0 - 20,0 bar
K- 07 25 07 20	Argon/helium	0 - 10,0 bar