



Ieejas spiediens
Max. 40 bar
Vides temperatūra
Max. 90 °C
Vielas temperatūra
max. 60 °C
Caurplūde
2500 l/min
Blīvējums
NBR
Korpuss
Aluminium
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design. Separate indication of input and working pressure on two pressure gauges. The pressure setting can be locked by pushing the button down. We recommend always using these controllers in conjunction with our K-07250615 and K-07250615 filters.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	DN
K- 07 25 08 11	G 1 1/2	0.5 - 6 bar	180.0	246.0 mm	50
K- 07 25 08 12	G 1 1/2	0.5 - 10 bar	180.0	246.0 mm	50
K- 07 25 08 13	G 1 1/2	0.5 - 16 bar	180.0	246.0 mm	50
K- 07 25 08 14	G 1 1/2	0.5 - 25 bar	180.0	246.0 mm	50
K- 07 25 08 15	G 2	0.5 - 6 bar	160.0	246.0 mm	50
K- 07 25 08 16	G 2	0.5 - 10 bar	160.0	246.0 mm	50
K- 07 25 08 17	G 2	0.5 - 16 bar	160.0	246.0 mm	50
K- 07 25 08 18	G 2	0.5 - 25 bar	160.0	246.0 mm	50