

# K-KONSTANT DRUCKREGLER STANDARD 2

Constant-pressure regulators



Ieejas spiediens  
Max. 25 bar (G 1/4 to G 1/2), Max. 40 bar (G 3/4 to G 1 1/2)  
Vides temperatūra  
Max. 90 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc for (G 1/4 to G 1/2), for Brass (G 3/4 to G 1 1/2)  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure regulators maintain a constant working pressure regardless of variations in the inlet pressure.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN
K- 07 25 03 98	G 3/4	0.5 - 3 bar	8700	116.0	93.0 mm	43.0	177.0	20
K- 07 25 03 99	G 3/4	0.5 - 6 bar	8200	116.0	93.0 mm	43.0	177.0	20
K- 07 25 04 00	G 3/4	0.5 - 10 bar	7830	116.0	93.0 mm	43.0	177.0	20
K- 07 25 04 01	G 3/4	0.5 - 16 bar	7400	116.0	93.0 mm	43.0	172.0	20
K- 07 25 04 02	G 3/4	0.5 - 25 bar	6500	116.0	93.0 mm	43.0	172.0	20
K- 07 25 04 03	G 1	0.5 - 3 bar	8700	116.0	81.0 mm	43.0	177.0	20
K- 07 25 04 04	G 1	0.5 - 6 bar	8200	116.0	81.0 mm	43.0	177.0	20
K- 07 25 04 05	G 1	0.5 - 10 bar	7830	116.0	81.0 mm	43.0	177.0	20
K- 07 25 04 06	G 1	0.5 - 16 bar	7400	116.0	81.0 mm	43.0	172.0	20
K- 07 25 04 07	G 1	0.5 - 25 bar	6500	116.0	81.0 mm	43.0	172.0	20
K- 07 25 04 08	G 1 1/4	0.5 - 3 bar	16000	114.0	126.0 mm	48.0	189.0	25
K- 07 25 04 09	G 1 1/4	0.5 - 6 bar	14000	114.0	126.0 mm	48.0	189.0	25
K- 07 25 04 10	G 1 1/4	0.5 - 10 bar	12160	114.0	126.0 mm	48.0	189.0	25
K- 07 25 04 11	G 1 1/4	0.5 - 16 bar	11000	114.0	126.0 mm	48.0	184.0	25
K- 07 25 04 12	G 1 1/4	0.5 - 25 bar	8500	114.0	126.0 mm	48.0	184.0	25
K- 07 25 04 13	G 1 1/2	0.5 - 3 bar	16000	114.0	114.0 mm	48.0	189.0	25
K- 07 25 04 14	G 1 1/2	0.5 - 6 bar	14000	114.0	114.0 mm	48.0	189.0	25
K- 07 25 04 15	G 1 1/2	0.5 - 10 bar	12160	114.0	114.0 mm	48.0	189.0	25
K- 07 25 04 16	G 1 1/2	0.5 - 16 bar	11000	114.0	114.0 mm	48.0	184.0	25
K- 07 25 04 17	G 1 1/2	0.5 - 25 bar	8500	114.0	114.0 mm	48.0	184.0	25