

Precision pressure regulators with continuous pressure supply



Ieejas spiediens
 Max. 16 bar
 Temperatūras diapazons
 -10 °C to +50 °C
 Darba vides
 Saspiests gaiss
 Caurplūde
 At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
 Korpusa
 Material: Grivory® (PA 66)
 Membrāna
 NBR
 Pieslēguma vītne
 Material: Die-cast zinc
 Iekšējā gaisa patēriņš
 2.6 l/min at P2 = 6 bar (depending on secondary pressure)
 Caurplūdes vērtības mērijums
 At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Precision diaphragm pressure regulators with self-relieving design and excellent flow rates in modern design for mounting side by side.
By assembling two or more controllers together, it is possible to supply several working air circuits with different pressures via a single supply line.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm
K- 07 25 09 66	G 1/4	0.1 - 1 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 67	G 1/4	0.1 - 2 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 68	G 1/4	0.2 - 4 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 69	G 1/4	0.5 - 8 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 70	G 1/4	0.5 - 10 bar	2200	52.0	128.5 mm	95.5
K- 07 25 09 71	G 3/8	0.1 - 1 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 72	G 3/8	0.1 - 2 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 73	G 3/8	0.2 - 4 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 74	G 3/8	0.5 - 8 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 75	G 3/8	0.5 - 10 bar	2700	52.0	128.5 mm	95.5
K- 07 25 09 76	G 3/8	0.1 - 1 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 77	G 3/8	0.1 - 2 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 78	G 3/8	0.2 - 4 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 79	G 3/8	0.5 - 8 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 80	G 3/8	0.5 - 10 bar	4300	63.0	149.5 mm	110.0
K- 07 25 09 81	G 1/2	0.1 - 1 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 82	G 1/2	0.1 - 2 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 83	G 1/2	0.2 - 4 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 84	G 1/2	0.5 - 8 bar	5000	63.0	149.5 mm	110.0
K- 07 25 09 85	G 1/2	0.5 - 10 bar	5000	63.0	149.5 mm	110.0