

Precision pressure regulators with continuous pressure supply



Ieejas spiediens  
 Max. 16 bar  
 Temperatūras diapazons  
 -10 °C to +50 °C  
 Darba vides  
 Saspiests gaiss  
 Caurplūde  
 At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar  
 Korpusa  
 Material: Grivory® (PA 66)  
 Membrāna  
 NBR  
 Pieslēguma vītne  
 Material: Die-cast zinc  
 Iekšējā gaisa patēriņš  
 2.6 l/min at P2 = 6 bar (depending on secondary pressure)  
 Caurplūdes vērtības mērijums  
 At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Precision diaphragm pressure regulators with self-relieving design and excellent flow rates in modern design for mounting side by side. &lt;br&gt;By assembling two or more controllers together, it is possible to supply several working air circuits with different pressures via a single supply line.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītne | Regulēšanas diapazons | Caurplūde nom.<br>l/min | A<br>mm | B        | C<br>mm |
|----------------|-------|-----------------------|-------------------------|---------|----------|---------|
| K- 07 25 09 66 | G 1/4 | 0.1 - 1 bar           | 2200                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 67 | G 1/4 | 0.1 - 2 bar           | 2200                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 68 | G 1/4 | 0.2 - 4 bar           | 2200                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 69 | G 1/4 | 0.5 - 8 bar           | 2200                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 70 | G 1/4 | 0.5 - 10 bar          | 2200                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 71 | G 3/8 | 0.1 - 1 bar           | 2700                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 72 | G 3/8 | 0.1 - 2 bar           | 2700                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 73 | G 3/8 | 0.2 - 4 bar           | 2700                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 74 | G 3/8 | 0.5 - 8 bar           | 2700                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 75 | G 3/8 | 0.5 - 10 bar          | 2700                    | 52.0    | 128.5 mm | 95.5    |
| K- 07 25 09 76 | G 3/8 | 0.1 - 1 bar           | 4300                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 77 | G 3/8 | 0.1 - 2 bar           | 4300                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 78 | G 3/8 | 0.2 - 4 bar           | 4300                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 79 | G 3/8 | 0.5 - 8 bar           | 4300                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 80 | G 3/8 | 0.5 - 10 bar          | 4300                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 81 | G 1/2 | 0.1 - 1 bar           | 5000                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 82 | G 1/2 | 0.1 - 2 bar           | 5000                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 83 | G 1/2 | 0.2 - 4 bar           | 5000                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 84 | G 1/2 | 0.5 - 8 bar           | 5000                    | 63.0    | 149.5 mm | 110.0   |
| K- 07 25 09 85 | G 1/2 | 0.5 - 10 bar          | 5000                    | 63.0    | 149.5 mm | 110.0   |