



Ieejas spiediens  
Max. 16 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Darba vides  
Micro-filtered, unoiled compressed air (0.01 µm)  
Atgaisošanas pieslēgums  
G 3/8 (for mounting a silencer)  
Manometra pieslēgums  
G 1/4  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc  
Iekšējā gaisa patēriņš  
1.5 - 6 l/min, depending on input pressure and control range

## Apraksts

With high flow rate and large secondary relief port. Diaphragm pressure regulators with large secondary relief port for applications requiring an extremely accurate working pressure, especially at high flow rates.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	C mm	D mm
K- 07 25 09 28	G 1/4	0.05 - 3 bar	700	82.0	43.5	159.0
K- 07 25 09 29	G 1/4	0.05 - 7 bar	1500	82.0	43.5	159.0
K- 07 25 09 30	G 3/8	0.05 - 3 bar	3000	82.0	43.5	159.0
K- 07 25 09 31	G 3/8	0.05 - 7 bar	5500	82.0	43.5	159.0
K- 07 25 09 32	G 1/2	0.05 - 3 bar	3000	82.0	43.5	159.0
K- 07 25 09 33	G 1/2	0.05 - 5 bar	4500	82.0	43.5	159.0
K- 07 25 09 34	G 1/2	0.05 - 7 bar	5500	82.0	43.5	159.0