

K-NEBELOEL PC-BEHAEI

SCHUTZK HANSA

Oil-mist lubricators



Ieejas spiediens
0.5 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Aizsarggrozs
Polyamide
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Pilienu aizsargs
PA
Tvertne
Polycarbonate (with bayonet lock)
Eļļas veids
CL 32 acc. to DIN 51517 - ISO VG 32
Caurplūdes vērtības mērijums
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar

Apraksts

Oil-mist lubricators with excellent flow rates in modern design. These devices can be used to top up oil automatically. A hose must be connected to the threaded nipple on the oil bowl for this purpose. When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 08 79	G 1/4	2800	52.0	183.0 mm	62.2
K- 07 25 08 80	G 3/8	2800	52.0	183.0 mm	62.2
K- 07 25 08 81	G 3/8	8000	63.0	208.2 mm	69.7
K- 07 25 08 82	G 1/2	8000	63.0	208.2 mm	69.7
K- 07 25 08 77	G 3/4	16000	85.0	270.4 mm	87.9
K- 07 25 08 78	G 1	16000	85.0	270.4 mm	87.9