

# K-NEBELOELER METALLBEHAE S T VARI0B

Oil-mist lubricators with metal bowl, incl. sight glass and metal sight dome



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)  
Vides temperatūra  
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)  
Vielas temperatūra  
max. 50 °C  
Caurplūde  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc  
Pilienu aizsargs  
PA  
Eļļas veids  
CL 32 acc. to DIN 51517 - ISO VG 32  
Caurplūdes vērtības mērijums  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | Caurpl_de nom.<br>l/min | A<br>mm | B        | C<br>mm |
|----------------|--------|-------------------------|---------|----------|---------|
| K- 07 25 09 14 | G 1/4  | 3400                    | 48.0    | 180.0 mm | 60.0    |
| K- 07 25 09 16 | G 3/8  | 4400                    | 48.0    | 180.0 mm | 60.0    |
| K- 07 25 09 18 | G 1/2  | 4600                    | 70.0    | 224.0 mm | 65.0    |
| K- 07 25 09 20 | G 3/4  | 7500                    | 70.0    | 224.0 mm | 65.0    |
| K- 07 25 09 22 | G 1    | 7500                    | 124.0   | 224.0 mm | 65.0    |