


K-NEBELOELER METALLBEHÄLTUNG STANDARD

Oil-mist lubricators with metal bowl and metal sight dome



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Eļļas veids
CL 32 acc. to DIN 51517 - ISO VG 32
Caurplūdes vērtības mērijums
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Proportional lubricators, oil can be filled under pressure.

Produkts

Apzīmējums	Vītnes	Caurplūde nom. l/min	A mm	C mm	D mm	DN
K- 07 25 08 88	G 1/4	1200	50.0	51.0	119.5	6
K- 07 25 08 91	G 3/8	1200	50.0	51.0	119.5	6
K- 07 25 08 94	G 3/8	2400	70.0	51.0	145.0	10
K- 07 25 08 97	G 1/2	4000	79.0	55.0	157.0	15
K- 07 25 09 00	G 3/4	9000	102.0	58.0	160.0	20
K- 07 25 09 03	G 1	9000	90.0	58.0	160.0	25
K- 07 25 09 06	G 1 1/4	9000	137.0	70.0	232.0	40
K- 07 25 09 09	G 1 1/2	9000	125.0	70.0	232.0	45