

# K-NEBELOELER PC-BEHAELTER MULTIFIX

Oil-mist lubricators with polycarbonate bowl



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Korpuss  
Die-cast zinc, Aluminium for G 1 variant  
Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)  
Drain valve  
Manual  
Eļļas veids  
CL 32 acc. to DIN 51517 - ISO VG 32  
Caurplūdes vērtības mērījums  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Proportional lubricators, oil can be filled under pressure.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 91	G 1/4	1900	47.8	167.8 mm	58.0	109.8	6	1
K- 07 25 00 94	G 3/8	1900	47.8	167.8 mm	58.0	109.8	10	1
K- 07 25 00 97	G 1/2	5000	68.8	198.2 mm	66.1	132.1	15	2
K- 07 25 01 00	G 3/4	5000	68.8	198.2 mm	66.1	132.1	20	2
K- 07 25 01 03	G 1	18000	100.0	324.3 mm	82.7	241.6	25	3