

K-NEBELOELER PC-BEHAEALTER VARIOBLOC

Oil-mist lubricators with polycarbonate bowl



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Korpuss
Die-cast zinc
Pilienu aizsargs
PA
Eļļas veids
CL 32 acc. to DIN 51517 - ISO VG 32
Caurplūdes vērtības mērijums
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 09 13	G 1/4	3400	48.0	171.0 mm	52.0
K- 07 25 09 15	G 3/8	4400	48.0	171.0 mm	52.0
K- 07 25 09 17	G 1/2	4600	70.0	224.0 mm	57.0
K- 07 25 09 19	G 3/4	7500	70.0	224.0 mm	57.0
K- 07 25 09 21	G 1	7500	124.0	224.0 mm	57.0