

K-BEFUELLEINHEIT 230V AC

HANSA

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Filling units, electrically operated, with 230 VAC / 5= Hz solenoid, adjustable filling time



Ieejas spiediens
2 - 10 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Aizsardzības veids
IP 65
Elektriskais pieslēgums
Connector type C, ISO 15217, 2 poles +PE
Ieslēgšanas ilgums
ED 100 %
Jaudas patēriņš DC
2.5 W
Pievilkšanas jauda maiņspriegumam 50 Hz
2.2 VA
Turēšanas jauda maiņspriegumam 50 Hz
1.6 VA
Caurplūde
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar
Outlets for G 1/2 and G 3/4
1/2
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Caurplūdes vērtības mērījums
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar

Apraksts

The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure. The unit consists of a 3/2-way valve and a filling valve (start-up valve). It is connected and disconnected by means of the 3/2-way valve. The filling time can be altered by turning the adjusting screw.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Jaudas patēriņš DC W	Pievilkšanas jauda maiņspriegumam 50 Hz VA	Turēšanas jauda maiņspriegumam 50 Hz VA	Vītne	Izeja	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 11 03	2.5	2.2	1.6	G 1/4	1/4	1300	104.0	117.8 mm	84.8
K- 07 25 11 04	2.5	2.2	1.6	G 3/8	1/4	1300	104.0	117.8 mm	84.8
K- 07 25 11 29	2.5	2.2	1.6	G 3/8	1/2	3400	126.0	150.3 mm	93.8
K- 07 25 11 30	2.5	2.2	1.6	G 1/2	1/2	3400	126.0	150.3 mm	93.8
K- 07 25 11 51	2.5	2.2	1.6	G 3/4	1/2	8750	170.0	177.7 mm	110.7
K- 07 25 11 52	2.5	2.2	1.6	G 1	1/2	8750	170.0	177.7 mm	110.7

Neskatoties uz rūpīgu pārbaudi, mēs nevaram garantēt visas šajā vietnē ievietotās informācijas precizitāti.