



Ieejas spiediens  
0 - 16 bar  
Temperatūras diapazons  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P2 = 6 bar, pressure drop  $\Delta p = 1$  bar  
Outlets for G 1/2 and G 3/4  
3/4  
Korpuss  
Material: Grivory® (PA 66)  
Pieslēguma vītne  
Material: Die-cast zinc  
Caurplūdes vērtības mērijums  
At P2 = 6 bar, pressure drop  $\Delta p = 1$  bar

## Apraksts

Closable ball valve in 3/2-way design, mechanically actuated. Toggle 90° rotatable and with switch position indicator: Traverse: Inlet port blocked - outlet port exhausted

Longitudinal: Inlet port and outlet port connected - exhaust blocked. Exhaust air can be collected.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Izeja	Caurplūde nom. l/min	A mm	B	C mm
K- 07 25 11 23	G 1/4	1/4	1900	52.0	87.5 mm	54.5
K- 07 25 11 24	G 3/8	1/4	1900	52.0	87.5 mm	54.5
K- 07 25 11 43	G 3/8	1/2	11000	63.0	127.0 mm	70.5
K- 07 25 11 44	G 1/2	1/2	11000	63.0	127.0 mm	70.5
K- 07 25 11 45	G 3/4	3/4	25000	85.0	144.7 mm	93.7
K- 07 25 11 46	G 1	3/4	25000	85.0	144.7 mm	93.7