

K-SCHALTVENTILE 3/2 VAROBLOC

On-off valves (3/2-way valves)



Aizsardzības veids
IP 65 acc. to DIN 40050
Caurplūde
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
Darba spiediens
3 to 10 bar
Caurplūdes vērtības mērījums
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

For pressurising and relieving pneumatic systems. Ideal as the main "on" valve for service units. The pressure in the line is exhausted when the valve is switched off.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Savienojums	Spriegums
K- 07 25 11 94	G 1/4	2200	48.0	147.0 mm	108.0	Device plug PG 9, type B, EN 175301-803	24 V DC
K- 07 25 11 95	G 3/8	2600	48.0	147.0 mm	108.0	Device plug PG 9, type B, EN 175301-803	24 V DC
K- 07 25 11 96	G 1/2	3300	70.0	157.0 mm	113.0	Device plug PG 9, type B, EN 175301-803	24 V DC
K- 07 25 11 97	G 3/4	3800	70.0	157.0 mm	113.0	Device plug PG 9, type B, EN 175301-803	24 V DC
K- 07 25 11 98	G 1	3800	124.0	157.0 mm	113.0	Device plug PG 9, type B, EN 175301-803	24 V DC