



Ieejas spiediens
0 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Outlets	Vītnes	Izeja	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 11 17	3 x G 1/4	G 1/4	3 x G 1/4	2700	52.0	65.5 mm	34.5
K- 07 25 11 18	3 x G 1/4	G 3/8	3 x G 1/4	3600	52.0	65.5 mm	34.5
K- 07 25 11 19	2 x G 3/8, 1 x G 1/4, 1 x G 1/2	G 3/8	2 x G 3/8, 1 x G 1/4, 1 x G 1/2	7250	63.0	80.5 mm	43.0
K- 07 25 11 20	2 x G 3/8, 1 x G 1/4, 1 x G 1/2	G 1/2	2 x G 3/8, 1 x G 1/4, 1 x G 1/2	7250	63.0	80.5 mm	43.0
K- 07 25 11 21	2 x G 3/4	G 3/4	2 x G 3/4	18000	85.0	109.5 mm	58.5
K- 07 25 11 22	2 x G 3/4	G 1	2 x G 3/4	18000	85.0	109.5 mm	58.5