



Izejas
4 (all sealed at delivery)
Caurplūde
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
Outlets for G 1/2 and G 3/4
Top / bottom G 3/8 / G 1/2, Front / back G 1/4
Outlets for G 1/4 and G 3/8
Top / bottom G 3/8, Front / back G 1/4
Caurplūdes vērtības mērījums
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

For removing unlubricated air when the manifold is flanged on upstream of the oil-mist lubricator. An integrated non-return valve prevents oil inflow from the oil-mist lubricator or the line.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Outlets	Vītnes	Caurpl_de nom. l/min	A mm	B
K- 07 25 11 99	4 (all sealed at delivery)	G 1/4	900	48.0	44.0 mm
K- 07 25 12 00	4 (all sealed at delivery)	G 3/8	900	48.0	44.0 mm
K- 07 25 12 01	4 (all sealed at delivery)	G 1/2	4000	70.0	56.0 mm
K- 07 25 12 02	4 (all sealed at delivery)	G 3/4	5000	70.0	56.0 mm
K- 07 25 12 03	4 (all sealed at delivery)	G 1	5000	124.0	56.0 mm