

# K-WTEH 2-TLG MET M ABLV TRO STANDAD

Service units with metal bowl and manual drain valve, metal sight dome



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)  
Regulēšanas diapazons  
0.5 to 10 bar (polycarbonate bowl / bowl guard) 0.5 to 16 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu\text{m}$  (Size 1 / Size 3), 40  $\mu\text{m}$  (Size 2 / Size 4)  
Korpuss  
Die-cast zinc / Aluminium, painted silver  
Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	DN	Ø manometram
K- 07 25 14 94	G 1/4	600	117.0	240.0 mm	106.5	6	50
K- 07 25 14 97	G 3/8	600	117.0	240.0 mm	106.5	6	50
K- 07 25 15 00	G 3/8	800	150.0	281.5 mm	120.5	10	63
K- 07 25 15 03	G 1/2	2100	175.0	302.0 mm	130.0	15	63
K- 07 25 15 06	G 3/4	4000	220.0	454.6 mm	190.6	20	63
K- 07 25 15 09	G 1	4000	220.0	454.6 mm	190.6	25	63