

K-WTEH 2-TLG MET MANO TROPF STAN-MI

Service units, 2-piece with metal bowl and pressure gauge, metal sight dome



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
350 l/min (2-piece), 300 l/min (3-piece)
Blīvējums
NBR
Poru attālums filtra elementā
5 µm
Korpuss
Die-cast zinc, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve
Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Compact, two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	C mm	D mm	DN
K- 07 25 14 90	G 1/8	0.5 - 10 bar	85.0	167.0 mm	65.0	102.0	5
K- 07 25 14 92	G 1/4	0.5 - 10 bar	85.0	167.0 mm	67.0	102.0	5