

K-WTEH 2-TLG PC SCHU H ABL STANDARD

Service units with polycarbonate bowl, bowl guard and semi-automatic drain valve



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Regulēšanas diapazons
0.5 to 10 bar (polycarbonate bowl / bowl guard) 0.5 to 16 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (Size 1 / Size 3), 40 μm (Size 2 / Size 4)
Korpuss
Die-cast zinc / Aluminium, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	DN	Ø manometram
K- 07 25 14 95	G 1/4	600	117.0	236.2 mm	106.5	6	50
K- 07 25 14 98	G 3/8	600	117.0	236.2 mm	106.5	6	50
K- 07 25 15 01	G 3/8	800	150.0	266.4 mm	120.5	10	63
K- 07 25 15 04	G 1/2	2100	175.0	299.4 mm	130.0	15	63
K- 07 25 15 07	G 3/4	4000	220.0	452.0 mm	190.6	20	63
K- 07 25 15 10	G 1	4000	220.0	452.0 mm	190.6	25	63