

K-WTEH 2-TLG PC SCHU MANO

HANSA

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Service units, 2-piece with polycarbonate bowl, bowl guard and pressure gauge



Ieejas spiediens
1.5 - 16 bar
Izejas spiediens
0.5 - 8 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Filtra smalkums
5.00 μm
Aizsarggrozs
Polyamide
Filtra elements
Cellpor (PE)
Korpuss
Material: Grivory® (PA 66)
Membrāna
NBR
Pieslēguma vītne
Material: Die-cast zinc
Pilienu aizsargs
PA
Tvertne
Polycarbonate (with bayonet lock)
Iekšējā gaisa patēriņš
Max. 1.5 l/min (depending on secondary pressure)
Caurplūdes vērtības mērījums
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two or three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Filtra smalkums μm	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 14 77	5.00	G 1/4	1800	104.0	225.0 mm	95.5	Semi
K- 07 25 14 78	5.00	G 3/8	1800	104.0	225.0 mm	95.5	Semi
K- 07 25 14 79	5.00	G 3/8	3500	126.0	257.0 mm	110.0	Semi
K- 07 25 14 80	5.00	G 1/2	3500	126.0	257.0 mm	110.0	Semi
K- 07 25 14 81	5.00	G 3/4	12000	170.0	329.0 mm	137.0	Semi
K- 07 25 14 82	5.00	G 1	12000	170.0	329.0 mm	137.0	Semi
K- 07 25 14 83	5.00	G 1/4	1800	104.0	243.0 mm	95.5	Auto
K- 07 25 14 84	5.00	G 3/8	1800	104.0	243.0 mm	95.5	Auto
K- 07 25 14 85	5.00	G 3/8	3500	126.0	274.0 mm	110.0	Auto
K- 07 25 14 86	5.00	G 1/2	3500	126.0	274.0 mm	110.0	Auto
K- 07 25 14 87	5.00	G 3/4	12000	170.0	343.0 mm	137.0	Auto
K- 07 25 14 88	5.00	G 1	12000	170.0	343.0 mm	137.0	Auto

Neskatoties uz rūpīgu pārbaudi, mēs nevaram garantēt visas šajā vietnē ievietotās informācijas precizitāti.