

K-WTEH 2-TLG PC SCHU WAND

H G

Service units, 2-piece with polycarbonate bowl, bowl guard and joiner for wall mounting, semi-automatic drain valve



Ieejas spiediens
Max. 10 bar
Vides temperatūra
Max. 70 °C
Vielas temperatūra
max. 70 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm
Atsperes korpuss
POM
Korpuss
Die-cast aluminium
Pilienu aizsargs
Brass/POM
Drain valve
Semi- or fully-automatic
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	Tipizmērs
K- 07 25 13 95	G 1/4	1.5 - 9 bar	1050	115.0	225.5 mm	82.5	143.0	300
K- 07 25 13 97	G 3/8	1.5 - 9 bar	1350	115.0	225.5 mm	82.5	143.0	300
K- 07 25 13 99	G 1/2	1.5 - 9 bar	1350	115.0	225.5 mm	82.5	143.0	300
K- 07 25 14 01	G 3/8	1.5 - 9 bar	3100	152.0	270.5 mm	104.0	166.5	400
K- 07 25 14 03	G 1/2	1.5 - 9 bar	3100	152.0	270.5 mm	104.0	166.5	400