

K-WTEH 2-TLG PC-BEHAEL MULTIFIX

Service units, 2-piece with polycarbonate bowl



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (BG 1 / BG 2), 40 μm (BG 3)
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve
Semi-automatic
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītne	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm	D mm	DN	Tipizmers
K- 07 25 01 29	G 1/4	0.5 - 10 bar	1100	92.8	192.1 mm	67.0	125.1	6	1
K- 07 25 01 32	G 3/8	0.5 - 10 bar	1100	92.8	192.1 mm	67.0	125.1	10	1
K- 07 25 01 35	G 1/2	0.5 - 10 bar	3500	134.8	246.3 mm	99.0	147.3	15	2
K- 07 25 01 38	G 3/4	0.5 - 10 bar	3500	134.8	246.3 mm	99.0	147.3	20	2
K- 07 25 01 41	G 1	0.5 - 10 bar	10500	200.0	381.8 mm	128.0	253.8	25	3