

# K-WTEH 2-TLG PC-BEHAEL SCHUTZK MULT

Service units, 2-piece with polycarbonate bowl and bowl guard



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu\text{m}$  (BG 1 / BG 2), 40  $\mu\text{m}$  (BG 3)  
Atsperes korpuss  
POM-brass  
Korpuss  
Die-cast zinc, Aluminium for G 1 variant  
Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)  
Drain valve  
Semi-automatic  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmers
K- 07 25 01 31	G 1/4	0.5 - 10 bar	1100	92.8	192.1 mm	67.0	125.1	6	1
K- 07 25 01 34	G 3/8	0.5 - 10 bar	1100	92.8	192.1 mm	67.0	125.1	10	1
K- 07 25 01 37	G 1/2	0.5 - 10 bar	3500	134.8	246.3 mm	99.0	147.3	15	2
K- 07 25 01 40	G 3/4	0.5 - 10 bar	3500	134.8	246.3 mm	99.0	147.3	20	2
K- 07 25 01 43	G 1	0.5 - 10 bar	10500	200.0	381.8 mm	128.0	253.8	25	3