

K-WTEH 3-TLG MET M ABLV TRO STANDAD

Service units with metal bowl and manual drain valve, metal sight dome



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Regulēšanas diapazons
0.5 to 10 bar (polycarbonate bowl / bowl guard) 0.5 to 16 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (G 1/4 / G 3/8 / G 1/2), 40 μm (G 3/8 / G 3/4 / G 1 / G 1 1/4 / G 1 1/2)
Korpuss
Die-cast zinc / Aluminium, painted silver
Pilienu aizsargs
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Produkts

| Apzīmējums | Vitnes | Caurplūde nom. l/min | A mm | B | C mm | DN | Ø manometram |
|----------------|---------|-------------------------|---------|----------|---------|----|--------------|
| K- 07 25 14 50 | G 1/4 | 600 | 172.0 | 184.5 mm | 51.0 | 6 | 50 |
| K- 07 25 14 57 | G 3/8 | 600 | 185.0 | 184.5 mm | 51.0 | 6 | 50 |
| K- 07 25 14 60 | G 3/8 | 1400 | 232.0 | 210.0 mm | 51.0 | 6 | 50 |
| K- 07 25 14 63 | G 1/2 | 3200 | 259.0 | 226.0 mm | 55.0 | 15 | 63 |
| K- 07 25 14 66 | G 3/4 | 3200 | 302.0 | 230.5 mm | 58.0 | 20 | 63 |
| K- 07 25 14 69 | G 1 | 3200 | 302.0 | 230.5 mm | 58.0 | 25 | 63 |
| K- 07 25 14 72 | G 1 1/4 | 5000 | 395.0 | 316.0 mm | 70.0 | 25 | 63 |
| K- 07 25 14 75 | G 1 1/2 | 5000 | 395.0 | 316.0 mm | 70.0 | 35 | 63 |