

# K-WTEH 3-TLG MET SICH WAND

## H G

Service units, 3-piece with metal bowl, sight glass and joiner for wall mounting, semi-automatic drain valve



Ieejas spiediens  
Max. 10 bar  
Vides temperatūra  
Max. 70 °C  
Vielas temperatūra  
max. 70 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu\text{m}$   
Atsperes korpuss  
POM  
Korpuss  
Die-cast aluminium  
Pilienu aizsargs  
Brass/POM  
Drain valve  
Semi- or fully-automatic  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	Tipizmērs
K- 07 25 14 31	G 3/4	1.5 - 9 bar	3750	295.0	280.5 mm	61.5	219.0	600
K- 07 25 14 33	G 1	1.5 - 9 bar	3750	295.0	280.5 mm	61.5	219.0	600