

# K-WTEH 3-TLG PC MONO STANDARD-MINI

Service units, 3-piece with polycarbonate bowl and pressure gauge



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
350 l/min (2-piece), 300 l/min (3-piece)  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5 µm  
Korpuss  
Die-cast zinc, painted silver  
Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)  
Drain valve  
Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Compact, two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	C mm	D mm	DN
K- 07 25 14 52	G 1/8	0.5 - 10 bar	130.0	151.5 mm	49.5	102.0	5
K- 07 25 14 54	G 1/4	0.5 - 10 bar	130.0	151.5 mm	49.5	102.0	5