


# K-WTEH 3-TLG PC MULTIFIX MINI

Service units, 3-piece with polycarbonate bowl



Ieejas spiediens  
Max. 12 bar (also for metal tank!)

Vides temperatūra  
Max. 60 °C

Vielas temperatūra  
max. 60 °C

Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

Blīvējums  
NBR

Poru attālums filtra elementā  
5  $\mu\text{m}$

Atsperes korpuss  
POM-brass

Korpuss  
Die-cast zinc

Pilienu aizsargs  
PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)

Drain valve  
Semi-automatic

Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Two or three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 01 06	G 1/8	0.5 - 10 bar	700	120.0	165.5 mm	63.0	102.5	5	0
K- 07 25 01 08	G 1/4	0.5 - 10 bar	700	120.0	165.5 mm	63.0	102.5	5	0