

# K-WTEH 3-TLG PC SCH MANO

## HANSA

**HANSA FLEX**  
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Service units, 3-piece with polycarbonate bowl, bowl guard and pressure gauge



Ieejas spiediens  
1.5 - 16 bar  
Izejas spiediens  
0.5 - 8 bar  
Temperatūras diapazons  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar  
Filtra smalkums  
5.00  $\mu\text{m}$   
Aizsarggrozs  
Polyamide  
Filtra elements  
Cellpor (PE)  
Korpuss  
Material: Grivory® (PA 66)  
Membrāna  
NBR  
Pieslēguma vītne  
Material: Die-cast zinc  
Pilienu aizsargs  
PA  
Tvertne  
Polycarbonate (with bayonet lock)  
Iekšējā gaisa patēriņš  
Max. 1.5 l/min (depending on secondary pressure)  
Caurplūdes vērtības mērījums  
At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Two or three-piece service units with excellent flow rates in modern design. <br>Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.<br>

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Filtra smalkums $\mu\text{m}$	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 14 37	5.00	G 1/4	1500	156.0	225.0 mm	95.5	Semi
K- 07 25 14 38	5.00	G 3/8	1500	156.0	225.0 mm	95.5	Semi
K- 07 25 14 39	5.00	G 3/8	3500	189.0	257.0 mm	110.0	Semi
K- 07 25 14 40	5.00	G 1/2	3500	189.0	257.0 mm	110.0	Semi
K- 07 25 14 41	5.00	G 3/4	12000	255.0	329.0 mm	137.0	Semi
K- 07 25 14 42	5.00	G 1	12000	255.0	329.0 mm	137.0	Semi
K- 07 25 14 43	5.00	G 1/4	1500	156.0	243.0 mm	95.5	Auto
K- 07 25 14 44	5.00	G 3/8	1500	156.0	243.0 mm	95.5	Auto
K- 07 25 14 45	5.00	G 3/8	3500	189.0	274.0 mm	110.0	Auto
K- 07 25 14 46	5.00	G 1/2	3500	189.0	274.0 mm	110.0	Auto
K- 07 25 14 47	5.00	G 3/4	12000	255.0	343.0 mm	137.0	Auto
K- 07 25 14 48	5.00	G 1	12000	255.0	343.0 mm	137.0	Auto

Neskatoties uz rūpīgu pārbaudi, mēs nevaram garantēt visas šajā vietnē ievietotās informācijas precizitāti.