

K-WTEH 3-TLG PC SCHU

VARIOBLOC

Service units, 3-piece with polycarbonate bowl and bowl guard



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
40 μm
Atsperes korpuss
POM
Korpuss
Die-cast zinc
Membrāna
NBR
Pilienu aizsargs
PA
Drain valve
Manual
Caurplūdes vērtības mērijums
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Regulēšanas diapazons | Caurpl_de nom. l/min | A mm | B | C mm |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|
| K- 07 25 22 86 | G 1/4 | 0.5 - 10 bar | 1500 | 144.0 | 201,0 mm | 68.0 |
| K- 07 25 22 85 | G 3/8 | 0.5 - 10 bar | 1800 | 144.0 | 201,0 mm | 68.0 |
| K- 07 25 22 84 | G 1/2 | 0.5 - 10 bar | 3400 | 210.0 | 247,0 mm | 98.0 |
| K- 07 25 22 83 | G 3/4 | 0.5 - 10 bar | 5000 | 210.0 | 247,0 mm | 98.0 |
| K- 07 25 22 82 | G 1 | 0.5 - 10 bar | 5000 | 264.0 | 247,0 mm | 98.0 |