

# K-WTEH 3-TLG PC SCHU WAND

## V G

Service units, 3-piece with polycarbonate bowl, bowl guard and joiner for wall mounting, fully-automatic drain valve



Ieejas spiediens  
Max. 10 bar  
Vides temperatūra  
Max. 70 °C  
Vielas temperatūra  
max. 70 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu\text{m}$   
Atsperes korpuss  
POM  
Korpuss  
Die-cast aluminium  
Pilienu aizsargs  
Brass/POM  
Drain valve  
Semi- or fully-automatic  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Produkts

Apzīmējums	Vitnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	Tipizmērs
K- 07 25 14 22	G 1/4	1.5 - 9 bar	1100	179.0	187.0 mm	44.0	143.0	300
K- 07 25 14 24	G 3/8	1.5 - 9 bar	1400	179.0	187.0 mm	44.0	143.0	300
K- 07 25 14 26	G 1/2	1.5 - 9 bar	1400	179.0	187.0 mm	44.0	143.0	300
K- 07 25 14 28	G 3/8	1.5 - 9 bar	2950	236.0	214.5 mm	48.0	166.5	400
K- 07 25 14 30	G 1/2	1.5 - 9 bar	2950	236.0	214.5 mm	48.0	166.5	400