

K-WTEH 3-TLG PC-BEHAEL S W

H G

Service units, 3-piece with polycarbonate bowl, bowl guard and joiner for wall mounting, semi-automatic drain valve



Ieejas spiediens
Max. 10 bar
Vides temperatūra
Max. 70 °C
Vielas temperatūra
max. 70 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm
Atsperes korpuss
POM
Korpuss
Die-cast aluminium
Pilienu aizsargs
Brass/POM
Drain valve
Semi- or fully-automatic
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Produkts

| Apzīmējums | Vitnes | Regulēšanas diapazons | Caurpl_de nom. l/min | A mm | B | C mm | D mm | Tipizmērs |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|---------|-----------|
| K- 07 25 14 21 | G 1/4 | 1.5 - 9 bar | 1100 | 179.0 | 187.0 mm | 44.0 | 143.0 | 300 |
| K- 07 25 14 23 | G 3/8 | 1.5 - 9 bar | 1400 | 179.0 | 187.0 mm | 44.0 | 143.0 | 300 |
| K- 07 25 14 25 | G 1/2 | 1.5 - 9 bar | 1400 | 179.0 | 187.0 mm | 44.0 | 143.0 | 300 |
| K- 07 25 14 27 | G 3/8 | 1.5 - 9 bar | 2950 | 236.0 | 214.5 mm | 48.0 | 166.5 | 400 |
| K- 07 25 14 29 | G 1/2 | 1.5 - 9 bar | 2950 | 236.0 | 214.5 mm | 48.0 | 166.5 | 400 |