

# K-WTEH KOMBI PC-BEHAELTER S H ABLV

Combination service units with polycarbonate bowl, bowl guard and manual drain valve



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)  
Vides temperatūra  
Max. 50 °C  
Vielas temperatūra  
max. 50 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
50  $\mu\text{m}$   
Korpuss  
Die-cast zinc, Spring bonnet; PA  
Pilienu aizsargs  
PA  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design. The pressure setting can be locked by pushing the knob down. Oil can be filled under pressure.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 08 45	G 1/4	0.5 - 10 bar	1400	67.0	217.0 mm	68.5
K- 07 25 08 47	G 1/4	0.5 - 16 bar	1000	67.0	217.0 mm	68.5
K- 07 25 08 49	G 3/8	0.5 - 10 bar	1400	67.0	217.0 mm	68.5
K- 07 25 08 51	G 3/8	0.5 - 16 bar	1000	67.0	217.0 mm	68.5
K- 07 25 08 53	G 1/2	0.5 - 10 bar	1400	65.0	217.0 mm	68.5
K- 07 25 08 55	G 1/2	0.5 - 16 bar	1000	65.0	217.0 mm	68.5
K- 07 25 08 57	G 3/4	0.5 - 10 bar	3400	97.0	296.5 mm	96.5
K- 07 25 08 59	G 3/4	0.5 - 16 bar	2800	97.0	296.5 mm	96.5
K- 07 25 08 61	G 1	0.5 - 10 bar	3400	93.0	296.5 mm	96.5
K- 07 25 08 63	G 1	0.5 - 16 bar	2800	93.0	296.5 mm	96.5