

K-WTEH KOMBI PC-BEHAELTER S H ABLV

Combination service units with polycarbonate bowl, bowl guard and manual drain valve



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 50 °C
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
50 μm
Korpuss
Die-cast zinc, Spring bonnet; PA
Pilienu aizsargs
PA
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design. The pressure setting can be locked by pushing the knob down. Oil can be filled under pressure.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 08 45	G 1/4	0.5 - 10 bar	1400	67.0	217.0 mm	68.5
K- 07 25 08 47	G 1/4	0.5 - 16 bar	1000	67.0	217.0 mm	68.5
K- 07 25 08 49	G 3/8	0.5 - 10 bar	1400	67.0	217.0 mm	68.5
K- 07 25 08 51	G 3/8	0.5 - 16 bar	1000	67.0	217.0 mm	68.5
K- 07 25 08 53	G 1/2	0.5 - 10 bar	1400	65.0	217.0 mm	68.5
K- 07 25 08 55	G 1/2	0.5 - 16 bar	1000	65.0	217.0 mm	68.5
K- 07 25 08 57	G 3/4	0.5 - 10 bar	3400	97.0	296.5 mm	96.5
K- 07 25 08 59	G 3/4	0.5 - 16 bar	2800	97.0	296.5 mm	96.5
K- 07 25 08 61	G 1	0.5 - 10 bar	3400	93.0	296.5 mm	96.5
K- 07 25 08 63	G 1	0.5 - 16 bar	2800	93.0	296.5 mm	96.5