

K-WTEH SERIE ONE M DRS

Service units, »ONE« Series, with pressure switch



Ieejas spiediens
Max. 10 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Aizsardzības veids
IP 65
Caurplūde
At 6,3 bar and $\Delta p = 1$ bar
Darba spiediens
0.5 - 8 bar
Spiediena slēdzis
Changeover contact
Poru attālums filtra elementā
20 μ m
Caurplūdes vērtības mērijums
At 6,3 bar and $\Delta p = 1$ bar

Apraksts

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Savienojums	Caurpl_de nom. l/min	A mm	B	C mm	Spriegums
K- 07 25 13 82	G 1/4"	2400	165.5	144.0 mm	35.0	24 V DC (for valves and pressure switch)
K- 07 25 13 83	G 3/8"	3300	165.5	144.0 mm	35.0	24 V DC (for valves and pressure switch)
K- 07 25 13 84	G 1/2"	4000	165.5	144.0 mm	35.0	24 V DC (for valves and pressure switch)