


# K-WTST SAFETY BK SCHA AN DR

## HANSA

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and pressure regulator



Ieejas spiediens  
2.5 - 16 bar  
Izejas spiediens  
0.5 - 8 bar  
Temperatūras diapazons  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Filtra elements  
Cellpor (PE) 5  $\mu\text{m}$   
Korpuss  
Material: Grivory® (PA 66)  
Membrāna  
NBR  
Pieslēguma vītne  
Material: Die-cast zinc  
Tvertne  
Polycarbonate (with bayonet lock) and bowl guard  
Iekšējā gaisa patēriņš  
Max. 1.5 l/min (depending on secondary pressure)  
Caurplūdes vērtības mērījums  
At P1 = 10 bar, P2 = 6.3 bar and pressure drop  $\Delta p = 1$  bar  
Atgaisošanas pieslēgums Lodveida krāns  
Silencer

## Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītne	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm
K- 07 25 15 20	G 1/4	2.5 - 8 bar	2000	156.0	128.5 mm	95.5
K- 07 25 15 21	G 3/8	2.5 - 8 bar	2000	156.0	128.5 mm	95.5
K- 07 25 15 22	G 3/8	2.5 - 8 bar	4300	189.0	149.5 mm	110.0
K- 07 25 15 23	G 1/2	2.5 - 8 bar	4300	189.0	149.5 mm	110.0
K- 07 25 15 24	G 3/4	2.5 - 8 bar	10000	255.0	191.0 mm	137.0
K- 07 25 15 25	G 1	2.5 - 8 bar	10000	255.0	191.0 mm	137.0