

# K-WTST SAFETY BKR SCHA AN DR MULTI

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and pressure regulator with lock cylinder



Ieejas spiediens  
2 - 16 bar  
Izejas spiediens  
0.5 - 10 bar  
Temperatūras diapazons  
Max. 60 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Atsperes korpuss  
POM  
Filtra elements  
Cellpor (PE) 5  $\mu\text{m}$   
Korpuss  
Die-cast zinc  
Membrāna  
NBR  
Tvertne  
Polycarbonate (with bayonet lock) and bowl guard  
Drain valve  
Semi-automatic  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Atgaisošanas pieslēgums Lodveida krāns  
Silencer

## Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

## Produkts

| Apzīmējums     | Vītnes | Regulēšanas diapazons | Caurpl_de nom.<br>l/min | A<br>mm | B        | C<br>mm |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|
| K- 07 25 15 11 | G 1/4  | 2 - 10 bar            | 1000                    | 128.0   | 137.8 mm | 94.0    |
| K- 07 25 15 12 | G 1/2  | 2 - 10 bar            | 4000                    | 189.0   | 200.8 mm | 122.0   |
| K- 07 25 15 13 | G 1    | 2 - 10 bar            | 12000                   | 241.7   | 282.8 mm | 157.0   |