

K-WTST SAFETY BKR SCHA AN FILR MULT

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and filter regulator with lock cylinder



Ieejas spiediens
2 - 16 bar
Izejas spiediens
0.5 - 10 bar
Temperatūras diapazons
Max. 60 °C
Darba vides
Saspiests gaiss
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Atsperes korpuss
POM
Filtra elements
Cellpor (PE) 5 μm
Korpuss
Die-cast zinc
Membrāna
NBR
Tvertne
Polycarbonate (with bayonet lock) and bowl guard
Drain valve
Semi-automatic
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Atgaisošanas pieslēgums Lodveida krāns
Silencer

Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 15 14	G 1/4	1000	219.1	137.8 mm	94.0	Semi-automatic
K- 07 25 15 15	G 1/2	4000	269.3	200.8 mm	122.0	Semi-automatic
K- 07 25 15 16	G 1	12000	410.8	282.8 mm	157.0	Semi-automatic